



Simple,  
secure  
vending.




## Express ToolBox™

Secure Point-of-Use Dispensing

This high-security device manages and controls consumable, while lowering costs, increasing productivity and reducing waste.

## Available Accessories\*\*

- 7" interactive display screen
- Vertical inner partition to vend narrow items
- Riser platform to vend short items
- V-channel mini helix to vend small, narrow items
- Spray Can Dispensing Kit to vend up to 12 spray cans
- Auger helix for vending small items (available in 30 coil pitch with 0.5 in / 1.27 cm slot depth)



V-channel & Mini Helix    Vertical Partition    Riser Platform    Flip Bar Pusher    Auger    Spray Can Dispenser

Each single helix shelf can hold 10 SKUs. Each large and dual helix shelf can hold 5 SKUs. Shelf height is 6 to 8 in / 15.24 to 20.32 cm. Single coil maximum capacity is 10 lbs / 4.54 kg. Maximum shelf capacity is 100 lbs / 45.36 kg.

## Suggested Inventory Items

The Express ToolBox is tailored to dispense small PPE items and cutting tools such as:

- Inserts
- Batteries
- Safety glasses
- Filters
- Tape
- Fasteners
- Cutting tool inserts
- Welding tips

## Express ToolBox Configurations

### Single Helix Configuration (2.5 in / 6.35 cm diameter)

Helix Count	5	7	8	9	10	12	15	18	24	32
Slot Depth (in)*	4.04	2.9	2.51	2.25	2.02	1.66	1.3	1.05	0.75	0.53
Slot Depth (cm)*	10.26	7.37	6.38	5.72	5.13	4.22	3.3	2.67	1.91	1.35

### Large Helix Configuration (3.75 in / 9.53 cm diameter)

Helix Count	4	5	7	9	10	12	15			
Slot Depth (in)*	4.1	3.45	2.58	2.05	2.01	1.55	1.24			
Slot Depth (cm)*	10.41	8.76	6.55	5.21	5.11	3.94	3.15			

### Dual Helix Configuration (5 in / 12.7 cm diameter)

Helix Count	5	7	9	10	12	15	18	24		
Slot Depth (in)*	4.04	2.9	2.25	2.02	1.66	1.3	1.05	0.75		
Slot Depth (cm)*	10.26	7.37	5.72	5.13	4.22	3.3	2.67	1.91		

© 2019 CribMaster. All Rights Reserved. The Information is Subject to Change Without Notice.  
D.MA.MKT.012b.3

## Express ToolBox Specs

### Main Exterior Dimensions

Height	72 in	182.88 cm
Width	39 in	99.06 cm
Depth	36 in	91.44 cm

### Weight

Main - 6 Shelf	544 lbs	247 kg
----------------	---------	--------

### Power Requirements

Amps	3	1.5 (EU)
Voltage	120	230 (EU)

### Operating Environment

Temperature	35°F to 110°F	1°C to 43°C
Humidity	20% to 85% (no condensation)	

### Technical Info

CE Compliant

Linux OS

### Helix Info

Helix Count	10	20	32
Slot Depth (in)*	1.87	0.96	0.53
Slot Depth (cm)*	4.75	2.44	1.35

\* Not the actual size of opening. Slot depth is measured from the peak of one spiral pitch to the next.

\*\*Sold separately